

United States Department of Commerce  
National Institute of Standards and Technology



---

## Certificate of Accreditation to ISO/IEC 17025:2017

---

NVLAP LAB CODE: 600306-0

**Technical Safety Services, LLC**  
Berkeley, CA

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,  
listed on the Scope of Accreditation, for:*

### **Calibration Laboratories**

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality  
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

---

2022-12-20 through 2023-12-31

*Effective Dates*



A handwritten signature in blue ink, reading "Dana S. Laman".

---

*For the National Voluntary Laboratory Accreditation Program*

**CALIBRATION LABORATORIES**

**NVLAP LAB CODE 600306-0**

**SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017**

<b>Technical Safety Services, LLC</b> 620 Hearst Avenue Berkeley, CA 94710 United States Allan Bier abier@techsafety.com phone: 510-845-5591 x 1152 URL: <a href="https://techsafety.com/">https://techsafety.com/</a>	<b>Fields of Calibration</b> Dimensional Mechanical Thermodynamic
---	--

**CALIBRATION AND MEASUREMENT CAPABILITIES (CMC) <sup>Notes 1,2</sup>**

Measured Parameter or Device Calibrated	Range	Expanded Uncertainty <sup>Notes 3</sup>	Remarks
<b>DIMENSIONAL</b>			
<b>LENGTH and DIAMETER; STEP GAGES (20/D05)</b>			
Micrometers Field calibrations available <sup>Note 4</sup>	(0.6 to 25) mm (25 to 50) mm (50 to 75) mm	1.2 µm 1.3 µm 1.5 µm	Gage Blocks
Calipers Field calibrations available <sup>Note 4</sup>	(0.6 to 150) mm	10 µm	Gage Blocks
<b>MECHANICAL</b>			
<b>MASS DETERMINATION (20/M08)</b>			
Mass Pieces	(0 to 2) g (2 to 80) g (80 to 200) g (200 to 1000) g (1 to 10) kg	0.009 mg 0.04 mg 0.2 mg 0.6 mg 8 mg	Troemner Ultra Class Mass Pieces (ASTM E617 Class 0)
<b>WEIGHING INSTRUMENTS (20/M16)</b>			
Scales and Balances Field calibrations available <sup>Note 4</sup>	1 mg to 1 g (1 to 200) g 200 g to 1 kg	0.06 mg 0.65 mg 1.3 mg	Troemner Ultra Class Mass Pieces (ASTM E617 Class 0)

2022-12-20 through 2023-12-31

*Effective dates*



*For the National Voluntary Laboratory Accreditation Program*


**CALIBRATION LABORATORIES**

**NVLAP LAB CODE 600306-0**

**CALIBRATION AND MEASUREMENT CAPABILITIES (CMC) Notes 1,2**

Measured Parameter or Device Calibrated	Range	Expanded Uncertainty Notes 3	Remarks
<b>THERMODYNAMIC</b>			
<b>LABORATORY THERMOMETERS, DIGITAL AND ANALOGUE (20/T03)</b>			
Digital and Analogue Thermometers Field calibrations available Note 4	(-95 to -40) °C (-40 to 140) °C (140 to 400) °C	0.070 °C 0.014 °C 0.059 °C	PRT w/ Fluke bath 9190A, Fluke bath 7341
<b>PRESSURE (20/T05)</b>			
Pneumatic Pressure Gages Field calibrations available Note 4	(0 to 15) PSIG (15 to 100) PSIG (100 to 500) PSIG	0.005 PSIG 0.02 PSIG 0.04 PSIG	Pressure Gages
<b>VACUUM AND LOW PRESSURE GAGES (20/T09)</b>			
Pneumatic Pressure Gages Field calibrations available Note 4	(0 to 3) in H <sub>2</sub> O (3 to 15) in H <sub>2</sub> O (15 to 40) in H <sub>2</sub> O	0.0012 in H <sub>2</sub> O 0.005 in H <sub>2</sub> O 0.027 in H <sub>2</sub> O	Pressure Gages
Vacuum Gages Field calibrations available Note 4	(-14 to 0) PSIV	0.006 PSIV	Vacuum Gages
<b>END</b>			

2022-12-20 through 2023-12-31  
Effective dates

  
For the National Voluntary Laboratory Accreditation Program

**CALIBRATION LABORATORIES**

**NVLAP LAB CODE 600306-0**

**Notes**

**Note 1:** A Calibration and Measurement Capability (CMC) is a description of the best result of a calibration or measurement (result with the smallest uncertainty of measurement) that is available to the laboratory's customers under normal conditions, when performing more or less routine calibrations of nearly ideal measurement standards or instruments. The CMC is described in the laboratory's scope of accreditation by: the measurement parameter/device being calibrated, the measurement range, the uncertainty associated with that range (see note 3), and remarks on additional parameters, if applicable.

**Note 2:** Calibration and Measurement Capabilities are traceable to the national measurement standards of the U.S. or to the national measurement standards of other countries and are thus traceable to the internationally accepted representation of the appropriate SI (Système International) unit.

**Note 3:** The uncertainty associated with a measurement in a CMC is an expanded uncertainty with a level of confidence of approximately 95 %, typically using a coverage factor of  $k = 2$ . However, laboratories may report a coverage factor different than  $k = 2$  to achieve the 95 % level of confidence. Units for the measurand and its uncertainty are to match. Exceptions to this occur when marketplace practice employs mixed units, such as when the artifact to be measured is labeled in non-SI units and the uncertainty is given in SI units (Example: 5 lb weight with uncertainty given in mg).

**Note 3a:** The uncertainty of a specific calibration by the laboratory may be greater than the uncertainty in the CMC due to the condition and behavior of the customer's device and specific circumstances of the calibration. The uncertainties quoted do not include possible effects on the calibrated device of transportation, long term stability, or intended use.

**Note 3b:** As the CMC represents the best measurement results achievable under normal conditions, the accredited calibration laboratory shall not report smaller uncertainty of measurement than that given in a CMC for calibrations or measurements covered by that CMC.

**Note 3c:** As described in Note 1, CMCs cover calibrations and measurements that are available to the laboratory's customers under *normal conditions*. However, the laboratory may have the capability to offer special tests, employing special conditions, which yield calibration or measurement results with lower uncertainties. Such special tests are not covered by the CMCs and are outside the laboratory's scope of accreditation. In this case, NVLAP requirements for the labeling, on calibration reports, of results outside the laboratory's scope of accreditation apply. These requirements are set out in Annex A.1.h. of NIST Handbook 150, Procedures and General Requirements.

**Note 4:** Uncertainties associated with field service calibration may be greater as they incorporate on-site environmental contributions, transportation effects, or other factors that affect the measurements. (This note applies only if marked in the body of the scope.)

**Note 6:** NVLAP accreditation is the formal recognition of specific calibration capabilities. Neither NVLAP nor NIST guarantee the accuracy of individual calibrations made by accredited laboratories.

2022-12-20 through 2023-12-31

*Effective dates*



*For the National Voluntary Laboratory Accreditation Program*